



## BEHR® FAST DRYING WATER-BASED WOOD STAIN

No. B4500 Series

Available in a Tint Base and  
Assorted Pre-tinted Colors

- Superior Color Control
- Dries in 1 Hour
- One-Coat Coverage
- Reworkable for Up To 48 Hours After Application
- Smooth Application & Easy Workability
- Less Odor than Oil-Based Products



Prep Before Use



1 Coat  
Coverage



Spread Rate:  
100 Sq. Ft./Qt.



Clean-Up:  
Soap & Water

**WHERE TO USE:** Properly prepared interior, smooth unfinished, unsealed or stripped wood surfaces, including floors.

### **SURFACE PREPARATION† (Proper surface preparation is required)**

- Surface must be dry, clean, and free of dirt, grease, glue, and existing coatings before staining.
- Sand the wood in the direction of the grain using fine-grit sandpaper (#150) until smooth.
- Remove all sanding dust.
- To ensure uniform acceptance of stain color and beautiful results, pretreat the wood with BEHR® Water-Based Pre-Stain Wood Conditioner following label directions.

- Stir stain thoroughly before and occasionally during use. Do not thin.
- Always test stain on an inconspicuous area of the wood to verify desired color.

### **STAIN APPLICATION**

- Apply stain in the direction of the grain with a brush or clean cloth.
- Allow the stain to penetrate 5-10 minutes to achieve desired color. The more time the stain is allowed to penetrate, the richer and darker the color will be.
- Remove stain that has not absorbed into the wood with a clean cloth. Wipe in the direction of the grain, while blending light and dark areas to obtain uniform color. Do not allow stain that has not penetrated into the wood to dry on the wood surface.
- To darken the color, apply a second coat after 1 hour, repeating directions above. Do not sand between coats of stain.

### **CLEAR FINISH APPLICATION**

- Allow stain to dry for a minimum of 1 hour (dry time may be extended due to high humidity, low temperatures, or inadequate ventilation).
- Complete your project by applying a BEHR Clear Protective Finish, following label directions.
- Recommended finishes include BEHR Fast-Drying Water-Based Polyurethane or BEHR Water-Based Spar Urethane. Slight ambering may occur when these clear finishes are applied over light-colored stains. Always spot test on an inconspicuous area to ensure satisfactory results.

### **DISPOSAL**

- For disposal of empty containers and unused product contact your household refuse collection service.

### **LIMITED WARRANTY**

- Visit [behr.com/warranty](http://behr.com/warranty) or call 1-800-854-0133 Ext. 2 for more information.

**†WARNING** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**⚠ WARNING** Cancer and Reproductive Harm –  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**WARNING IRRITANT** CONTAINS: ETHYLENE GLYCOL, CARBON BLACK AND ISOTHIAZOLONE. MAY CAUSE AN ALLERGIC SKIN REACTION AND DAMAGE TO ORGANS (KIDNEY) THROUGH PROLONGED OR REPEATED EXPOSURE. MAY CAUSE EYE, SKIN, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH-approved for organic vapors with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN-DO NOT TAKE INTERNALLY.**

**PLEASE SEE PRODUCT LABEL FOR SPECIFIC WARNINGS. WARNINGS MAY VARY BETWEEN PRODUCTS AND OR COLORS.**



©2019 Behr Process Corporation  
Santa Ana, CA 92705 U.S.A. • [behr.com](http://behr.com)  
V.O.C. (C.O.V.) <275 g/L • REV. 7/19