



## Solid Color Concrete Stain

- Interior/Exterior Flat Finish
- Siliconized 100% Acrylic
- Weather Resistant
- Chemical & Hot-Tire Resistant

No. 800 White Base

No. 830 Deep Base

### **IMPORTANT! DO NOT OPEN CONTAINER WITHOUT READING INSTRUCTIONS. PROTECT FROM FREEZING.**

FOR TINT BASES – DO NOT USE WITHOUT THE ADDITION OF TINTING COLORANTS

#### WHERE TO USE

- Properly prepared Interior or Exterior surfaces such as: Concrete, Masonry Walls, Basements, Patios, Sidewalks, Driveways\*, Garage Floors\*, Tennis Courts, Cement Blocks, Pillars and Brick. Not for use on surfaces subject to hydrostatic pressure.
- \*Driveways and Garage Floors - Lack of proper surface preparation and/or over-application can lead to automobile tires lifting the product from the surface.

**CAUTION:** Stained surfaces may become slippery when wet. Use caution when walking on surface when moisture is present. Use a product such as BEHR PREMIUM™ NON-SKID NO. 970 to help prevent slipping.

#### PREPARATION† (The following steps are recommended for best results.)

##### New and Uncoated Concrete or Masonry Surfaces:

- New concrete must cure for a minimum of 30 days.
- For proper penetration and adhesion of topcoat, use a product such as BEHR PREMIUM™ CONCRETE & MASONRY CLEANER & ETCHER NO. 991 to clean and etch the surface. Remove mildew stains with a product such as BEHR PREMIUM MOLD & MILDEW STAIN REMOVER NO. 62. Follow all label instructions.
- Apply a product such as BEHR PREMIUM CONCRETE & MASONRY BONDING PRIMER NO. 880 to increase adhesion of topcoat to the surface. Follow all label instructions.

##### Painted, Stained or Sealed Concrete:

- *Option 1* - To completely strip the entire surface, use a product such as BEHR PREMIUM CONCRETE & MASONRY PAINT STRIPPER NO. 992. Follow all label instructions.
- *Option 2* - To recoat over an existing coating, remove any loose or peeling paint and scuff sand the surface.
- Use a product such as BEHR PREMIUM CONCRETE & MASONRY DEGREASER & CLEANER NO. 990 to clean previously coated surfaces in sound condition.
- Use a product such as BEHR PREMIUM CONCRETE & MASONRY CLEANER & ETCHER NO. 991 to clean and etch any bare concrete surface. Follow all label instructions.

**LIMITED WARRANTY** BEHR PROCESS CORPORATION warrants that this product meets Behr's manufacturing specifications. If this product does not meet these specifications, Behr Process Corporation will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **This guarantee excludes (1) labor and costs of labor for application or removal of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

**BEHR**  
A Masco Company

©2011 BEHR PROCESS CORPORATION  
Santa Ana, CA 92704 U.S.A. • behr.com  
V.O.C. (C.O.V.) <100 g/L • REV. 11/11

- Spot prime all uncoated areas with a product such as BEHR PREMIUM CONCRETE & MASONRY BONDING PRIMER NO. 880 to increase adhesion of topcoat to the surface. Follow all label instructions.

#### APPLICATION

- DO NOT THIN. Intermix all cans of same product to ensure color uniformity. Stir stain before and occasionally during application.
- Use product when air and surface temperatures are between 50-90°F (10-32°C).
- Apply a thin, even coat using a 1/4"-3/8" nap roller cover, pad applicator or a nylon/polyester brush at a spread rate of 400-600 sq. ft. (37-56 m<sup>2</sup>) per gallon. Use long, even strokes in one direction to avoid lap lines.
- Since concrete varies in texture/porosity, two coats may be required for uniform color appearance. Apply a second coat (in a criss-cross direction) if uniformity is needed. Recoat after 2-4 hours. Periodic touch-ups may be necessary.

#### DRY TIME

- Allow 24 hours for light foot traffic. Allow 72 hours before subjecting surface to automotive tires, repositioning planters or furniture. Park tires on corrugated cardboard for 14 days after applying stain. After two weeks, dry stained surface may be cleaned with a mild, non-abrasive liquid detergent.

#### CLEAN UP

- Use soap and water.
- Properly dispose of all soiled rags and **protect unused product from freezing.**
- For disposal of empty containers and unused paint, contact your household refuse collection service.

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

**WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.**