



BEHR PREMIUM PLUS® Interior Texture Paint

- Easy to Apply
- Ideal for Hiding Imperfections
- Reinforced with Interwoven Fibers for Added Durability

No. 559 White
Ceiling "Popcorn" Finish

IMPORTANT: DO NOT OPEN CAN WITHOUT READING THESE INSTRUCTIONS. PROTECT FROM FREEZING.

WHERE TO USE

Primed or low-sheen surfaces. Ideal for ceilings in Living Rooms, Dining Rooms, Bedrooms, Hallways and Kitchens.

PREPARATION†

Remove loose paint, wash off any dirt and grease with detergent, remove mildew stains with a mildew stain removing product. Scuff sand glossy surfaces. Countersink nailheads, repair imperfections and sand smooth. Remove all dust with a damp cloth and allow to dry. Allow new stucco, plaster and masonry to cure for 30 days before priming.

PRIME

Use a product such as BEHR® ALL-IN-ONE PRIMER & SEALER NO. 75. On new drywall in low-moisture rooms, use a product such as BEHR DRYWALL PRIMER & SEALER NO. 73

APPLICATION

Use product when the surface and air temperatures are between 50-90°F (10-32°C). **Stir thoroughly using a 5-gallon stir stick. Stir for 2 minutes or until product is well blended.** Coverage is 100-200 sq. ft. (9-18 m²) per 2 gallon container depending on application technique and surface condition. **Initial Application:** Apply product to a 3' x 3' section using a **looped roller**. Continue to work in 3' x 3' sections until the entire surface is complete. Allow to dry at least 4 hours. If necessary, apply a second coat using the same process. Note: additional coats will increase textured effect. **Designer Texture Effect:** Apply product to a 3' x 3' section using a **looped roller** and allow to set 5 minutes. Follow the specific technique instructions in the BEHR PREMIUM PLUS® Texture Paint guide. Continue to work in 3' x 3' sections and overlap slightly into the existing section until the entire surface is complete. Allow to dry at least 4 hours. Once the texture finish has dried 24-48 hours, to change color and increase durability, apply a product such as BEHR PRIMER NO. 75 and topcoat with a product such as BEHR PREMIUM PLUS paint or apply BEHR PREMIUM PLUS ULTRA paint and primer in one. Refer to paint label for further instruction.

DRY TIME

Dries in 4 hours at 75°F (23°C) and 50% humidity. Longer dry time required in cooler temperatures and in higher humidity. Surface will fully cure in 1 week.

CLEAN-UP & STORAGE

Use soap and water. Properly dispose of all soiled rags and **protect unused product from freezing**. To recycle or properly dispose of paint in your community, contact your local household refuse collections service.

Visit behr.com for painting tips, project advice and color coordination with the ColorSmart by BEHR® Tool, or download the ColorSmart by BEHR App on your mobile device.

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

***LIFETIME LIMITED WARRANTY** Behr Process Corporation warrants to the original residential consumer purchaser the performance of this product as described on this label for so long as you reside in your home. THIS WARRANTY IS NOT VALID WHEN THE PRODUCT IS NOT PROPERLY APPLIED TO A PROPERLY PREPARED SURFACE OR CARED FOR IN ACCORDANCE WITH THE LABEL DIRECTIONS. This warranty is not transferable. If this product is found not to perform as specified upon inspection by our representative during the warranty period, Behr Process Corporation will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. **This warranty excludes (1) labor and costs of labor for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a Behr Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH-approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.

BEHR
A Masco Company

©2016 BEHR PROCESS CORPORATION
Santa Ana, CA 92704 U.S.A. • behr.com
V.O.C. (C.O.V.) <50 g/L • REV. 04/16