



BEHR PREMIUM™ AEROSOL: Metallic, Hammered, and Textured Finishes

- Indoor/outdoor use
- Corrosion Resistant
- Excellent Adhesion

METALLIC

B060144C	Gold Gloss
B060244C	Oil Rubbed Bronze Satin
B060444C	Copper Gloss
B060544C	Soft Iron Satin
B060644C	Vintage Gold Gloss
B060744C	Nickel Satin
B060844C	Titanium Gloss
B061744C	Champagne Gold Matte
B061844C	Dark Steel Gloss
B062044C	Antique Copper Gloss
B062244C	Burnished Amber Matte

HAMMERED

B060944C	Black Gloss
B061444C	Dark Bronze Gloss
B061644C	White Gloss
B062844C	Copper Gloss
B062944C	Gold Gloss

TEXTURED

B061544C	Black Matte
----------	-------------



Protect
from Freezing



15-30 minutes
Dry to Touch
<1 hr or greater
than 24 Recoat time



1.4 sq metres
(15 sq ft) -
1.8 sq metres
(20 sq ft) Coverage



Mineral Spirits
Clean-Up

BEHR PREMIUM™ Aerosol features an enhanced formulation that combines paint and primer† in a single can, delivering a premium, durable finish. Designed for both indoor and outdoor uses.

BEHR PREMIUM™ Aerosol can be used on wood, metal, cast stone, and wicker. Weather and corrosion resistant, it delivers a reliable, long-lasting finish. The unique, ergonomic shape of the BEHR PREMIUM™ Aerosol can and its comfortable tip deliver a superior spray experience that fights fatigue so you can create a smooth finish every time.

†A Primer coat may be needed on some surfaces.

PREPARATION

The surface must be clean, free of dust, grease, wax, peeling paint, mold or mildew. If washing is necessary, use a non-soapy detergent or a TSP substitute. Rinse well and allow to dry.

†**Peeling or Checked Paint:** Scrape off loose paint and sand to a smooth surface. Sanding or removal of paint containing lead is hazardous.

***Glossy Surfaces:** For maximum adhesion, scuff sand the surface thoroughly before painting.

APPLICATION

Eye protection is recommended. For best results, use at room temperature. Cover adjacent areas to protect from overspray. Shake can vigorously for one minute after mixing ball begins to

rattle and often during use. Hold can upright, moving from side-to-side while spraying lightly and evenly about 30 cm (12") from area being painted. Two to three thin coats produce best results.

CLEAN-UP & DISPOSAL

Clear spray valve immediately after use by turning can upside down and spraying until only clear gas is released. If spray nozzle becomes clogged, remove and clean. Do not stick pins or wire into can opening. Clean fresh overspray with mineral spirits or paint thinner. Remove dried paint with paint remover, but test small area first to ensure paint remover does not damage substrate. Please consider donating any unused product. For recycling or disposal information contact your local household refuse collection service.

Visit behr.ca for painting tips, project advice and colour coordination with the ColourSmart by BEHR™ Tool, or download the ColourSmart by BEHR App on your mobile device.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact Health Canada at 1-866-225-0709 or log on to www.canada.ca/en/health-canada/services/home-safety/lead-based-paint.

***LIMITED WARRANTY** For one year from the date of purchase, Behr Process Corporation warrants to the original consumer purchaser, (1) that the product meets Behr's manufacturing specifications, and (2) the performance of this product when applied according to the label instructions and specifications. If this product is found not to perform as specified on the label within one year from the date of purchase, Behr Process Corporation will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. **This warranty excludes (1) labour and costs of labour for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some provinces do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. **To the extent permitted by applicable law, any implied warranties including the implied warranties of merchantability and of fitness for a particular purpose, are limited to the duration of this express warranty.** Some provinces do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from provinces to provinces. To obtain warranty service, call 1-800-661-1591. Behr Process Corporation reserves the right to inspect any and all application of the product prior to processing your claim made under this warranty.

To consult with a Behr Paint Company Representative, call 1-800-661-1591.

EXTREME DANGER! VERY FLAMMABLE, POISON, IRRITANT, CONTENTS UNDER PRESSURE. CONTENTS MAY CATCH FIRE. CONTENTS HARMFUL. FUMES HARMFUL. MAY IRRITATE EYES AND SKIN. CONTAINER MAY EXPLODE WHEN HEATED. Do not smoke. Do not swallow. Avoid contact with eyes, skin and clothing. Do not breathe fumes. Do not puncture. Do not burn. Use only with adequate ventilation. Wear a mask/respirator while handling the product. Keep away from flames, such as pilot light, and any object that sparks, such as an electric motor. Keep out of reach of children. Wear eye protection and protective clothing. Store away from heat. **FIRST AID TREATMENT:** May contain: ACETONE; BUTYL ACETATE; PROPANE; TITANIUM DIOXIDE; ISOBUTANE; GROUND CALCIUM CARBONATE; 1-METHOXY-2-PROPYL ACETATE; METHYL ETHYL KETONE; STODDARD SOLVENT; CARBON BLACK; 3-ETHOXYPROPIONIC ACID ETHYL ESTER; SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.; DISTILLATES (PETROLEUM), HYDROTREATED LIGHT; SILICON DIOXIDE; AND NAPHTHA (PETROLEUM), HYDROTREATED HEAVY. If swallowed, call Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes rinse with water for 15 – 20 minutes. If on skin rinse with water. If inhaled move person to fresh air.

