



BEHR PREMIUM® Concrete, Brick & Tile Wet-Look Sealer

No. 985 Hi-Gloss

- High-Gloss Clear Finish
- Excellent Topcoat Over Paints & Stains
- 100% Acrylic for Maximum Durability
- Interior/Exterior & Vertical/Horizontal
- Ideal for Pavers



Spread Rate:
200-450 Sq. Ft.



Dry Time:
1 Hr. Dry to Touch
4 Hr. Recoat



Clean-Up:
Soap & Water



Protect
from Freezing

CAUTION: Surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.

WHERE TO USE

Use on previously Coated/Uncoated, Vertical/Horizontal, Interior/Exterior surfaces such as: Pavers, Concrete, Mexican Tile and Unglazed Tiles, Brick, Aggregate, Natural and Artificial Stone, Masonry and Stucco. Not recommended for Wood, Metal, Granite, Marble, Terrazzo, areas immediately adjacent to pools, or areas subject to hydrostatic pressure. Do not use over oil-based products.

PREPARATION †

(Proper surface preparation is required.) All surfaces must be clean, sound, dry and free of any dirt, oil and grease. **Uncoated Concrete or Masonry Surfaces:** Allow new surfaces to cure 30 days. Clean and etch surface using a product such as a muriatic acid etcher (read and follow all manufacturer's label directions) to achieve a textured profile similar to 150 grit sandpaper. **Painted Surfaces-Concrete:** For a painted surface in sound condition, use a product to clean and prepare the surface. Stamped concrete requires the use of a cleaner to remove release agent prior to sealing. If the coating is failing or peeling, use a paint stripper to remove old coating or scrape/sand down to a sound concrete surface. Scuff sand glossy surfaces. Clean and spot etch any exposed concrete. Remove all dust with a damp cloth, allow to dry.

APPLICATION

DO NOT THIN. Stir or shake before applying. Use product when surface and air temperatures are between 50 - 80° F (10 - 27° C). Do not apply in direct sunlight, on wet surfaces, or if rain/heavy dew is expected within 24 hours. Apply a thin coat using a nylon/polyester brush, 1/4" - 3/8" nap roller, high quality pad applicator or a high quality pump sprayer with an adjustable tip. If sprayed, backroll for uniform thickness. Additional coats (no more than 4) may be added for higher gloss and added protection. Failure to properly prepare and completely dry the

surface or over application may lead to a milky white appearance. Follow all label instructions. NOTE: Horizontal surface may be subject to excessive wear. Periodic touch-ups may be necessary.

DRY TIME

Longer dry time required in cooler temperatures and higher humidity. Allow to dry 24 hours for light foot traffic. 72 hours to reposition furniture/heavy foot traffic and park tires on corrugated cardboard for 14 days. Clean with a mild, non-abrasive liquid detergent after 30 days.

DISPOSAL

Properly dispose of all soiled rags. For disposal of empty containers and unused product contact your household refuse collection service.

† WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

LIMITED WARRANTY Behr Process Corporation warrants that this product meets Behr's manufacturing specifications. If this product does not meet these specifications, Behr Process Corporation will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **This guarantee excludes (1) labor and costs of labor for application or removal of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.

BEHR
A Masco Company

©2014 Behr Process Corporation
Santa Ana, CA 92704 U.S.A. • behr.com
V.O.C. (C.O.V.) <100 g/L • REV. 3/16