



BEHR® Interior/Exterior Bonding Primer

- Adheres to Tough-to-Paint Surfaces
- Reduces Need for Sanding Dense, Glossy Surfaces
- Improves Topcoat Adhesion
- Works Under Alkyd, Oil and Water-Based Topcoats
- Quick Recoat Time
- Tintable up to 59 mL of Colourant per 3.78 L

No. 432 White



30 Min Dries to Touch
1 Hr Ready to Topcoat



28 - 37 m²
Coverage per 3.78 L



Soap & Water
Clean-Up



Protect
from Freezing

WHERE TO USE

Over properly prepared uncoated and previously painted Interior/Exterior surfaces. Ideal for Kynar®, PVC vinyl, Formica®, glass, tile, glazed brick, fiberglass, chalky paints, glossy finishes, architectural plastics and metals. If using as a primer for epoxies, lacquers, products containing xylene or other hot solvents, allow to dry for 24 hours before topcoating; test for compatibility in a discrete area first before full coat application. Not recommended for floors or horizontal surfaces subject to prolonged water contact.

PREPARATION

All surfaces must be properly prepared and cleaned. While BEHR® Bonding Primer is formulated to adhere without sanding, it is recommended that a small area be tested for adhesion prior to beginning the job. Remove loose paint, wash off chalk, dirt and grease with detergent, rinse well and allow to dry. Remove mildew stains with a mildew stain removing product. Remove all dust with a damp cloth, allow to dry. Remove loose rust, peeling paint and mill scale with a scraper, wire brush or sandpaper. Clean bare metal surfaces in accordance with The Society for Protective Coatings (SSPC) specifications.

APPLICATION

Apply when air and surface temperatures are between 10 – 32° C. Use a high quality 10 – 13 mm nap roller cover on smooth surfaces or 13 – 19 mm nap roller cover on semi-rough or porous surfaces, nylon/polyester brush or an airless sprayer (.015 – .021" spray tip, 60 mesh filter). Stir primer occasionally. Do not thin if using a roller or brush; however, if using a sprayer and thinning is required, thin with water at a rate of no more than 237 mL per 3.78 L. Topcoat within 14 days. For dramatic colour changes, tint primer with up to 59 mL of colourant per 3.78 L.

DISPOSAL

For disposal of empty containers, unused paint and soiled rags, contact your household refuse collection service.

Visit behr.com for painting tips, expert project advice and the perfect colour coordination with the ColourSmart by BEHR™ Tool.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact Health Canada at 1-866-225-0709 or log on to www.canada.ca/en/health-canada/services/home-safety/lead-based-paint.

***LIMITED WARRANTY** For one year from the date of purchase, Behr Process Corporation warrants to the original consumer purchaser, (1) that the product meets Behr Process Corporation's manufacturing specifications, and (2) the performance of this product when applied according to the label instructions and specifications. If this product is found not to perform as specified on the label within one year from the date of purchase, Behr Process Corporation will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. The clause of limitation of liability which follows is inapplicable in Quebec. **This warranty excludes (1) labour and costs of labour for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory. To the extent permitted by applicable law, any implied warranties including the implied warranties of merchantability and of fitness for a particular purpose, are limited to the duration of this express warranty.** The above provisions are not intended to operate where prohibited by law. This limited warranty is the only warranty provided by Behr Process Corporation unless extended by a provincial consumer statute. To obtain warranty service, call 1-800-661-1591, or contact Behr Process Corporation at 2750 Centre Avenue N.E., Calgary, AB T2A 2L3. Behr Process Corporation reserves the right to inspect any and all application of the product prior to processing your claim made under this warranty.

To consult with a Behr Paint Company Representative, call 1-800-661-1591

MAY IRRITATE EYES AND SKIN. Avoid contact with eyes, skin and clothing. Do not breathe fumes. Keep out of reach of children. Wear eye protection and protective clothing. Use only with adequate ventilation. **FIRST AID TREATMENT:** Contains NÉPHELINE SYENITE, TITANIUM DIOXIDE, AND TALC. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes rinse with water for 20 minutes. If on skin rinse well with water. If inhaled, move person to fresh air.

