



BEHR® Interior/Exterior Metal Primer

- Recommended for Use on Clean or Sound Rusty Metal Surfaces
- Direct-to-Rust Application with Minimal Surface Preparation
- Improves Topcoat Adhesion
- Rust-Inhibitive
- Quick Recoat Time
- High-hide
- Tintable up to 118 mL of Colourant per 3.78 L

No. 435 White



30 Min Dries to Touch
1 Hr Ready to Topcoat



33 - 42 m²
Coverage per 3.78 L



Soap & Water
Clean-Up



Protect
from Freezing

WHERE TO USE

Over properly prepared uncoated and previously painted Interior/Exterior ferrous and non-ferrous metal surfaces. Ideal for ferrous metal surfaces, such as: Steel, Carbon Steel, Stainless Steel, Cast Iron, Wrought Iron, Galvanized Steel; and non-ferrous metal surfaces, such as: Brass, Aluminum, Copper, Lead, Nickel, Tin, Titanium, Zinc and Metal Alloys.

PREPARATION

All surfaces must be properly prepared, cleaned and primed on the same day. Remove all loose or peeling paint; wash off chalk, dirt and grease with mild detergent, rinse well and allow to dry. Remove mildew stains with a mildew stain removing product. Scuff sand glossy surfaces and repair imperfections. Remove all loose dust and rust particles with a wire brush and dry cloth. In some cases, scraping or sanding may be needed to allow the primer to adhere. Do not use if surface is structurally unsound or severely deteriorated.

APPLICATION

Apply when air and surface temperatures are between 4 – 32°C. Use a high quality 6 – 10 mm nap roller cover, nylon/polyester brush or an airless sprayer (.011” – .017” spray tip, 60 mesh filter). Stir primer occasionally. Do not thin if using a roller or brush; however, if using a sprayer and thinning is necessary to maintain workability, thin with clean water at a rate of no more than 237 mL per 3.78 L.

DISPOSAL

For disposal of empty containers, unused paint and soiled rags, contact your household refuse collection service.

Visit behr.com for painting tips, expert project advice and the perfect colour coordination with the ColourSmart by BEHR™ Tool.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

LIMITED WARRANTY For one year from the date of purchase, Behr Process Corporation warrants to the original consumer purchaser, (1) that the product meets Behr Process Corporation's manufacturing specifications, and (2) the performance of this product when applied according to the label instructions and specifications. If this product is found not to perform as specified on the label within one year from the date of purchase, Behr Process Corporation will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. The clause of limitation of liability which follows is inapplicable in Quebec. **This warranty excludes (1) labour and costs of labour for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory. To the extent permitted by applicable law, any implied warranties including the implied warranties of merchantability and of fitness for a particular purpose, are limited to the duration of this express warranty.** The above provisions are not intended to operate where prohibited by law. This limited warranty is the only warranty provided by Behr Process Corporation unless extended by a provincial consumer statute. To obtain warranty service, call 1-800-661-1591, or contact Behr Process Corporation at 2750 Centre Avenue N.E., Calgary, AB T2A2L3. Behr Process Corporation reserves the right to inspect any and all application of the product prior to processing your claim made under this warranty.

To consult with a Behr Paint Company Representative, call 1-800-661-1591

MAY IRRITATE EYES AND SKIN. Avoid contact with eyes, skin and clothing. Do not breathe fumes. Wear eye protection and protective clothing. Use only with adequate ventilation. Keep out of reach of children. **FIRST AID TREATMENT:** Contains TITANIUM DIOXIDE, CALCINED KAOLIN, POLYURETHANE SOLUTION AND MAGNESIUM POTASSIUM SILICATE. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes rinse with water for 20 minutes. If on skin rinse well with water. If inhaled, move person to fresh air.

