



## BEHR® Interior/Exterior Oil-Based Stain-Blocking Primer & Sealer

- Blocks Heavy Tannin and Water Stains
  - Blocks Stains from Smoke and Fire Damage
  - Vapor Barrier
  - Helps Inhibit Rust
  - Recommended for Use Under Latex or Oil Topcoats
  - Mildew Resistant Finish
  - Tintable up to 118 ml of Colourant per 3.78 L
- No. 434 White



4-6 Hrs. Dries to Touch  
12-24 Hrs. Ready to Topcoat



23-37m<sup>2</sup>  
Coverage per 3.78 L



Mineral Spirits  
Clean-Up



Protect  
from Freezing

### WHERE TO USE

Over properly prepared uncoated and previously painted Interior/Exterior surfaces. Ideal for well-bonded Wallpaper, Steel, Wrought Iron and Wood.

### PREPARATION

All surfaces should be properly prepared and cleaned. Remove loose paint, wash off chalk, dirt, and grease with detergent, rinse and allow to dry. Wash bare metal. Rinse and allow to dry. Remove mildew stains with a mildew stain removing product. Scuff sand glossy surfaces and repair imperfections. Remove all dust with a damp cloth, allow to dry. For new or uncoated wood, use a product such as BEHR PREMIUM® No. 63 All-In-One Wood Cleaner.

### APPLICATION

Apply when air and surface temperatures are between 7 – 32°C. Stir primer occasionally. Do not thin. Product is formulated for use at package consistency only. Use a high quality 10 – 13 mm nap roller cover, natural bristle brush or an airless sprayer (.015 – .019" spray tip, 60 mesh filter). Spot prime patched areas first, followed with a complete primer coat. Topcoat within 30 days. Two coats may be required. Bright or deep colours require a tinted primer. Have primer tinted close to topcoat colour with no more than 118 ml of colourant per 3.78 L.

### DISPOSAL

For disposal of empty containers, unused paint and soiled rags, contact your household refuse collection service.

Visit [behr.com](http://behr.com) for painting tips, expert project advice and the perfect colour coordination with ColourSmart by BEHR™ Tool.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact Health Canada at 1-866-225-0709, or log on to [www.canada.ca/en/health-canada/services/home-safety/lead-based-paint](http://www.canada.ca/en/health-canada/services/home-safety/lead-based-paint).

**LIFETIME LIMITED WARRANTY** Behr Process Corporation warrants to you, the original residential consumer purchaser, the performance of this product as described on this label for so long as you reside in your home. THIS WARRANTY IS NOT VALID WHEN THE PRODUCT IS NOT PROPERLY APPLIED TO A PROPERLY PREPARED SURFACE OR CARED FOR IN ACCORDANCE WITH THE LABEL DIRECTIONS. This warranty is not transferable. If this product is found not to perform as specified on the label during the warranty period, Behr Process Corporation will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. The clause of limitation of liability which follows is inapplicable in Quebec. **This warranty excludes (1) labour and costs of labour for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** The above provisions are not intended to operate where prohibited by law. This limited warranty is the only warranty provided by Behr Process Corporation unless extended by a provincial consumer statute. To obtain warranty service, call 1-800-661-1591, or contact Behr Process Corporation at 2750 Centre Avenue N.E., Calgary, AB T2A 2L3. Behr Process Corporation reserves the right to inspect any and all application of the product prior to processing your claim made under this warranty.

To consult with a Behr Paint Company Representative, call 1-800-661-1591.

**MAY IRRITATE EYES AND SKIN.** Avoid contact with eyes, skin and clothing. Do not breathe fumes. Keep out of reach of children. Wear eye protection and protective clothing. Use only with adequate ventilation. Keep out of reach of children. Keep away from flames or sparks. **FIRST AID TREATMENT:** Contains TALC; DISTILLATES (PETROLEUM); HYDROTREATED LIGHT; NAPHTHA (PETROLEUM); HYDROTREATED HEAVY; TITANIUM DIOXIDE; CALCIUM CARBONATE; MAGNESIUM POTASSIUM SILICATE; AND XYLENE. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes rinse with water for 20 minutes. If on skin rinse well with water. If inhaled, move person to fresh air.

