



BEHR® WINDOW & TRIM ADVANCED HYBRID SEALANT

Ideal for: Baseboards, Window Frames, Door Frames, Trim, Molding, Siding, Stairs, Skirtings, Window Sills, Corner Joints, Pipes and Vents

PRODUCT INFORMATION

- Use for sealing connection joints and for transitional seal between building materials.
- Strong bond to difficult substrates.
- All-weather application; wet surface/in-rain application.
- Weatherproof & waterproof.
- Exceptional flexibility.
- Unique applicator for adjustable delivery of sealant.
- Paint-ready (brush/roll) in 1 hour; spray paint immediately
- Won't shine through or discolor paint.
- Reduced dirt pick-up.
- Non-yellowing.
- Asphalt-compatible.
- Easy water clean-up.
- Each 3.2 fl oz pressure pack canister will cover 19 linear feet with a 3/16" bead.
- For exterior/interior use.

DIRECTION FOR USE

All surfaces must be clean and free of dust, chalk, oil, grease, wax, polish, mold and mildew stains, rust, loose material and all other foreign substances. Remove the nozzle cover, pull tab, then adjust rotating cap following MIN/MAX arrow to control application rate. Press handle to apply. Smooth the sealant before the skin forms using a dry tool with a concave profile. Do not use water or soapy water for this operation. Allow 1 hour for sealant skin to form before painting with a brush/roller, or spray paint immediately. Turn back the rotating cap to stop the product flow and avoid accidental triggering. If the cap is turned to MIN, the nozzle cap can be removed for cleaning. Excess dried sealant must be cut or scraped away. Use backer rod for gaps larger than 1/2" x 1/2". Replace nozzle cap after use. Use within 6 months of opening. Clean tools, equipment and excess uncured material with mineral spirits, solvent or cleaning wipes.

⚠ WARNING Cancer and Reproductive Harm – www.P65Warnings.ca.gov

WARNING IRRITANT MAY IRRITATE EYES, SKIN, AND RESPIRATORY TRACT. CONTENTS UNDER PRESSURE. DO NOT PUNCTURE OR INCINERATE CONTAINER. DO NOT EXPOSE TO HEAT OR STORE AT TEMPERATURES ABOVE 120°F. CONTAINS LIMESTONE, N-[3-(TRIMETHY-OXSILYL)PROPYL]-1, 2-ETHANEDIAMINE, TIN, DIBUTYLBIS (2,4-PENTANEDIONATO-0,0')-, (OC-6-11)-, CRYSTALLINE SILICA AND TITANIUM DIOXIDE. METHANOL MAY FORM DURING CURING. Do not breathe fumes. Do not get in eyes, on skin or on clothing. Do not swallow. Handle with care. Use only in a well ventilated area or wear a respirator. Wear protective clothing including safety glasses and gloves. Wash thoroughly after handling. Store container in a cool, dry area with cap tightly sealed. **FIRST AID:** If in eyes or on skin, rinse with water for at least 15 minutes. If on clothes, remove clothing. If inhaled, move person to fresh air. If swallowed, call a Poison Control Center or doctor immediately. Do not induce vomiting.

KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.

