



DECKplus® Semi-Transparent Waterproofing Wood Finish - Penetrating Oil

No. 4633 - Cedar Naturaltone

No. 4630 - Redwood

No. 4629 - Chocolate

- Enhances the Natural Beauty of Wood
- Tintable to Custom Colours
- Easy to Apply and Maintain
- Waterproofing Protection
- Dirt and Mildew Resistant Finish
- For Decks, Fences & Siding



Must Prep
Before Applying
Wood Finish



1 Coat Application



Spread Rate:
Covers 23-28 m²
(250-300 sq. ft.)



Clean-Up:
Mineral Spirits
or Paint Thinner

CAUTION: Finished surfaces may become slippery when wet.

WHERE TO USE

- Recommended for properly prepared new to slightly weathered, unsealed exterior wood surfaces (0-5 years exposure) such as: Decks, Railings, Shakes, Shingles, Siding, Fences, and Wood Patio Furniture.

SURFACE PREPARATION† (Proper Surface Preparation is Required.)

- For failing coatings or to remove loose wood fibres, use a product such as BEHR PREMIUM® No. 64 Wood Stain & Finish Stripper followed by BEHR PREMIUM No. 63 All-In-One Wood Cleaner to neutralize the wood.
- When No. 64 is not needed, a product such as No. 63 MUST be used to remove mill glaze and clean the wood surface. After using either No. 64 or No. 63, rinse thoroughly with a garden hose or pressure washer. When rinsing with a pressure washer, use the broadest spray pattern while keeping the nozzle at least 60 cm (24") away from the surface.
- Allow the area to dry at least 24 hours before coating.
- Lightly sand to remove remaining wood fibres/fuzz. See behr.ca for additional product information.

APPLICATION

- **For best results, a pad applicator is recommended over large deck areas.**
- Must apply between 5-32°C.
- *Do not apply if rain is expected within 4 hours of product application. Resists rain 4 hours after application.
- Avoid applying in direct sunlight or to hot surfaces. Do not use if rain is expected within 24 hours.
- The surface must be completely dry before application.
- Intermix multiple containers to ensure colour uniformity.
- Stir product occasionally throughout application.
- Test product for penetration and colour on a small hidden area before proceeding.
- Use a natural bristle brush for areas requiring more accuracy. Use of rollers should be limited to rough surfaces only. Use 10 mm nap or longer when appropriate.
- Lightly saturate the surface and back-brush any excess finish.
- Be sure to eliminate puddling and evenly distribute the finish. Maintain a wet edge when applying.
- Apply product end-to-end or to board lengths to prevent lap marks. Avoid applying finish too heavily.
- One coat application. For optimum performance, coat all accessible sides.

MAINTENANCE

- When colour has faded and water is readily absorbed by the substrate, prep/clean with a product such as BEHR PREMIUM No. 63, allow to dry, and apply a new/fresh coat of wood finish.
- Product can be applied annually if needed.

DRY TIME

- Dry to touch after 2-4 hours depending on wood porosity. 24 hours before foot traffic. 72 hours for full cure.

DISPOSAL

- For disposal of empty containers and unused product contact your household refuse collection service.

1 YEAR LIMITED WARRANTY

- Visit behr.ca/warranty or call 1-800-661-1591 for more information

***WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

A quality product that contains a mildewcide will assist in providing a finish that is resistant to mildew, provided that all existing mildew is removed prior to application. While this product does contain a mildewcide, it will not prevent mildew growth.

CAUTION: Finished surfaces may become slippery when wet.

ATTENTION: Les surfaces recouvertes d'un enduit peuvent devenir glissantes lorsqu'elles sont mouillées.

LIMITED WARRANTY If this product is found to be defective upon inspection by an expert, Behr Process Corporation will, at its option, and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. This warranty is not transferable. If you believe this product is defective, contact Behr Process Corporation at 2750 Centre Avenue N.E., Calgary, AB T2A2L3. The cost of transportation or shipping, if any, are to be assumed by the consumer. The clause of limitation of liability which follows is inapplicable in Quebec: **This warranty excludes (1) labour and costs of labour for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** The above provisions are not intended to operate where prohibited by law. This limited warranty is the only warranty provided by Behr Process Corporation unless extended by a provincial consumer statute.

DANGER OF COMBUSTION. CONTENTS HARMFUL. MAY IRRITATE EYES AND SKIN. Avoid contact with eyes, skin and clothing. Do not breathe fumes. Do not swallow. Wear eye protection and protective clothing. Wear a mask/respirator while handling the product. Keep out of reach of children. **FIRST AID TREATMENT:** CONTAINS WHITE MINERAL OIL, ALKYD RESIN, HYDROTREATED LIGHT PETROLEUM DISTILLATE, AND MEDIUM ALIPHATIC PETROLEUM SOLVENT NAPHTHA. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes rinse with water for 20 minutes. If on skin rinse well with water. If inhaled, move person to fresh air.

©2020 Behr Process Corporation
Canadian Office
Bureau canadien • Calgary, Alberta
REV. 5/20 • behr.ca • 41013835
VOC/COV <250 g/L

