



BEHR PREMIUM® Solid Color Waterproofing Stain & Sealer

- For Decks, Fences & Siding
- Durable Advanced 100% Acrylic
- Self-Priming
- Enhanced UV Protection
- Mildew Resistant Finish

No. 5011 Tintable White
No. 5013 Deep Base
No. 50533 Cedar Naturaltone
No. 50129 Chocolate
No. 50330 Redwood
No. 50117 Russet
No. 50104 Cordovan Brown



Must Prep
Before Staining



2 Thin Coats
Recommended



Spread Rate:
1st Coat 200-400 Sq. Ft.
2nd Coat 400-800 Sq. Ft.



Soap & Water
Clean-Up

CAUTION: Stained surfaces may become slippery when wet.

WHERE TO USE

- Recommended for properly prepared new to heavily weathered or cracking wood surfaces (0 to 15+ years exposure) such as: Decks, Railings, Shakes, Shingles, Siding, Roofs, Fences, Wood Patio Furniture and Composites.

SURFACE PREPARATION† (Proper Surface Preparation is Required.)

- To remove failing coatings or to remove loose wood fibers, use a product such as BEHR PREMIUM® No. 64 Wood Stain & Finish Stripper followed by BEHR PREMIUM No. 63 All-In-One Wood Cleaner to neutralize the wood.
- When stripping is not needed, the surface **MUST** be prepared with a product such as No. 63 Wood Cleaner to remove mill glaze and clean the wood surface.
- After using either No. 64 or No. 63, rinse thoroughly with a garden hose or pressure washer. When rinsing with a pressure washer, use the broadest spray pattern while keeping the nozzle at least 24" away from the surface.
- Allow the area to dry at least 24 hours before coating.
- If needed, lightly sand to remove any wood fibers/fuzz.
- See behr.com for additional product information.

APPLICATION

- Must apply between 35-90° F and temperature must stay above 35° F for the next 12 hours.
- Avoid applying in direct sunlight or to hot surfaces.
- Coating will resist rain after 4 hours.
- The surface must be completely dry before application.
- No primer needed on most woods. However, Redwood, Cedar, Cypress and other "bleeding" woods may cause discoloration of white and pastel colors; therefore prime the above type woods with one coat of a product such as BEHR PREMIUM PLUS® No. 436 Exterior Multi-Surface Primer & Sealer. See label for additional instructions.
- For multiple gallons, combine into larger container for color uniformity.
- Stir product occasionally throughout application.

- Test product for penetration and color on a small hidden area before proceeding.
- Use a 3/8" nap roller, nylon/polyester brush, pad applicator or airless sprayer (.015 - .019" tip, 60 mesh filter).
- If thinning is required, thin with water at a rate of no more than 1/2 pint per gallon.
- Maintain a wet edge when applying.
- Always back-brush and apply product end to end or to board lengths to prevent lap marks.
- Over application of stain will lead to surface failure including peeling and cracking.
- For optimum performance, coat all accessible sides.
- Two thin coats recommended.

DRY TIME

- 1-2 hours before recoat. Wait 24-48 hours before light foot traffic. 72 hours for full cure.
- Additional dry time may be needed in cooler temperatures and higher humidity.

DISPOSAL

- For disposal of empty containers and unused product contact your household refuse collection service.

†WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

A quality product that contains a mildewcide will assist in providing a finish that is resistant to mildew, provided that all existing mildew is removed prior to application. While this product does contain a mildewcide, it will not prevent mildew growth.

LIMITED WARRANTY

Behr Process Corporation warrants customer satisfaction with this product for 25 years on vertical surfaces and for 10 years on horizontal surfaces from date of purchase, when applied to a properly prepared surface according to label directions. Color fading and slight natural graying of the wood may occur during this period, especially in areas exposed to heavy foot traffic or excessive weather. If you are not satisfied with this product, Behr Process Corporation will, at its option and upon proof of purchase, either furnish an equivalent amount of new product or refund the purchase price. **This warranty is made to the original residential product purchaser and is not transferable. This warranty excludes (1) labor and costs of labor for application or removal of any product or (2) any incidental or consequential damages, whether based upon breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

To consult with a Behr Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15-20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.



©2019 Behr Process Corporation
Santa Ana, CA 92705 U.S.A. • behr.com
V.O.C. (C.O.V.) <100 g/L • REV. 7/19